



TOTAL PROTECT PLUS





REF « TPP »

Anti-slip overshoe with safety cap and anti puncture outsole

- Composition: Rubber + protective toe cap in aluminum/titanium + outsoles (keylar and steel)
- Professional use: Prevents injuries in the work place: slips, toe crushing and puncture damages.
- ✓ Antipuncture outsole : full Kevlar outsole + steel midsole at the heel
- ✓ Aluminium/titanium toe cap : Ultra light!
- ✓ Outstanding grip coefficient
- ✓ Stretch fit structure: 4 Sizes to cover from 34 to 50
- ✓ Color code to track sizes
- ✓ Can be adapted to most kind of footwear
- ✓ Reusable waterproof
- ✓ Tiger-grip ® antislip sole with self cleaning studs

Certifications

PPE REGULATION (EU): 2016/425

(personal protective equipment)

 (ϵ) **EUROPEAN STANDARDS**

> CE certification: 0075/1344/161/08/16/0963

- NF EN ISO 20345 / 2011
- O NF EN 12568
- O NF EN 13287
- Oil resistance (FO)

CE PPE CERTIFIED Risk II

Certified organism: CTC N° 0075/69367 Lyon - France



AMERICAN STANDARDS

- ASTM F 2413 –11:
 - Toe cap
 - Puncture resistance
- ASTM F 2913

NF EN 13287 – Antislip properties

Certification SRC = SRA + SRB

SRB: Anti-slip coefficient on steel floors with glycerin

SRA: Anti-slip coefficient on ceramic floors with detergent

| Surface | Contact with | Standard ISO 13287 | TOTAL PROTECT PLUS results | | | | |
|---------|--------------|--------------------|----------------------------|--|--|--|--|
| Steel | Oil | SRB = 0.18 | + 340% = 0.62 | | | | |
| Ceramic | Detergent | SRA = 0.32 | +140% = 0.54 | | | | |
| | Water | - | 0.62 | | | | |

- NF EN 12568: Toe cap resistance and antipuncture tests :
 - × 200 joules resistance and resistant to crushing under max.load of 1500 DaN
 - × Puncture resistance



Full Kevlar antipuncture outsole and steel midsole at the heel part to protect against puncture whatever the shoe extension

Antistatism: The overshoe meets antistatic and ESD properties.

The shoe and overshoe combination must necessarily be tested by the user

Sizes



| restricted | | S | | | | М | | | | L | _ | | | XL | |
|------------|----|----|----|----|-----|----|-----|-----|-----|-----|----|------|------|------|------|
| EU Sizes | 34 | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 + |
| UK Sizes | 1 | 2 | 3 | 4 | 5 | 6 | 6,5 | 7 | 8 | 9 | 10 | 10,5 | 11 | 12 | 13 + |
| US Woman | 4 | 5 | 6 | 7 | 7,5 | 8 | 8,5 | 9,5 | 10 | 11 | | | | | |
| US Man | | | | | 5,5 | 6 | 7 | 8 | 8,5 | 9,5 | 10 | 11 | 11,5 | 12,5 | 13 + |

For a proper use of the overshoes, it is important to ensure that the overshoes fit neatly over the user's footwear

Storage and maintenance



- Hand washable Let them dry naturally
- Store in a dry place, away from temperature variation
- Do not use below a temperature of -20°c.

Design and manufacturing: TIGER-GRIP ENGINEERING



contact@tigergrip.com





31700 BEAUZELLE, France