



SAFETY JOGGER

PROFESSIONAL



Light

SLOAN 01 LOW

SLOAN

Fashionable, comfortable and slip-resistant ESD sneaker that offers reliable protection

Upper	Mesh, Synthetic
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Phylon/Rubber
Safety standard	O1 / ESD, FO, SRC
Size range	EU 35-42 / UK 3.0-8.0 US 5.5-10.5 / CM 23.0-27.0
Sample weight	0.265 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



FUC



BLU



Non-marking outsole

Non-marking outsoles do not leave color marks on the ground.




Breathable upper

Increased moisture and temperature management for extended wearer comfort.




Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.




Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

SAFETY JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:
Catering, Cleaning, Food & beverages, Medical

Environments:
Dry environment, Extreme slippery surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Mesh, Synthetic			
	Upper: permeability to water vapor	mg/cm²/h	2.87	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	21	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm²/h	63	≥ 2
	Lining: water vapor coefficient	mg/cm²	290	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	Phylon/Rubber			
	Outsole abrasion resistance (volume loss)	mm³	118	≤ 150
	Outsole slip resistance SRA: heel	friction	0.40	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.23	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.27	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	76	0.1 - 100
	Heel energy absorption	J	34.1	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com