



Medium


## BESTGIRL S3

Classic, low-cut safety shoe with a female touch

Upper	Barton Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Safety standard	S3 / SRC
Size range	EU 35-42 / UK 3.0-8.0 US 5.5-10.5 / CM 23.5-27.0
Sample weight	0.480 kg
Norms	EN ISO 20345:2011 ASTM F2413:2018



217



### Oil & fuel resistant

The outsole is resistant against oil and fuel.



### Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



### Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Mining, Logistics, Oil & Gas, Industry

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	<b>Barton Action Leather</b>			
	Upper: permeability to water vapor	mg/cm²/h	1.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	22.9	≥ 15
Lining	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm²/h	60.5	≥ 2
	Lining: water vapor coefficient	mg/cm²	484.1	≥ 20
Footbed	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm³	29.1	≤ 150
	Outsole slip resistance SRA: heel	friction	0.38	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	114.5	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	27	≥ 20
Toecap	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	NA
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	NA
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	16.5	≥ 14

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL   PROFESSIONAL   TACTICAL   TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com