



Medium

CERES S3

Low-cut safety shoe in nubuck, designed for ladies

Upper	Nubuck Action Leather
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Toecap	Composite
Safety standard	S3 / HRO, SRC
Size range	EU 35-42 / UK 3.0-8.0 US 5.5-10.5 / CM 23.0-27.0
Sample weight	0.470 kg
Norms	EN ISO 20345:2011 ASTM F2413:2018



210




Composite toecap
Metalfree and lightweight, no thermal or electrical conductivity



Water resistant Upper (WRU)
Prevents penetration of water if not permanently exposed to high levels.



SJ Flex
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Mining, Logistics, Oil & Gas, Industry

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nubuck Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	3.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	27.3	≥ 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	86.9	≥ 2
	Lining: water vapor coefficient	mg/cm ²	695.4	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	NA
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	NA
	Impact resistance toecap (clearance after impact 200J)	mm	18.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	≥ 14

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.